


### Oferta supraveghere video 2008

Imagine	Cod	Specificatii tehnice	Pret
<b>Camere de tip dome</b>			
	<b>MC-D308F</b>	Camera de supraveghere video color de tip dom; Senzor <b>1/4" Sharp color CCD</b> Rezolutie <b>420TVL</b> ; Iluminare minima 1 Lux; <b>Lentila 3.6 mm (63 grade)</b> ; Procesor DSP Sharp; Nivel semnal/zgomot >48db; Tensiune de alimentare 12V cc; Consum maxim 200 mA; Include lentila. Necesita alimentator.	<b>110 lei</b>
	<b>MC-D308SN</b>	Camera de supraveghere video color de tip dom; Senzor <b>1/3" Sony SUPER HAD CCD</b> ; Rezolutie <b>420TVL</b> , Iluminare minima 0,8 LUX <b>Lentila 3.6 mm (74 grade)</b> ; Procesor DSP Sony; Nivel semnal/zgomot >48db; Tensiune de alimentare 12V cc; Consum maxim 200 mA; Include lentila. Necesita alimentator.	<b>140 lei</b>
	<b>MC-D129F</b>	Camera de supraveghere video color de tip dom DAY/NIGHT; Senzor <b>1/4" Sharp color CCD</b> Rezolutie <b>420TVL</b> ; Iluminare minima 0 LUX (IR pornit); <b>Lentila 3.6 mm (63 grade)</b> ; Iluminator <b>12 leduri IR</b> - distanta iluminata pe timp de noapte maxim 10 m; Procesor DSP Sharp; Nivel semnal/zgomot >48db; Tensiune de alimentare 12V cc; Consum maxim 400 mA; Include lentila si iluminator infrarosu. Necesita alimentator.	<b>120 lei</b>
	<b>MC-D129SN</b>	Camera de supraveghere video color de tip dom DAY/NIGHT; Senzor <b>1/3" Sony SUPER HAD CCD</b> ; Rezolutie <b>420TVL</b> , Iluminare minima 0 LUX (IR pornit) <b>lentila 3.6 mm (74 grade)</b> ; Iluminator <b>12 leduri IR</b> , distanta iluminata pe timp de noapte maxim 10 m. Procesor DSP Sony; Nivel semnal/zgomot >48db; Tensiune de alimentare 12V cc; Consum maxim 400 mA; Include lentila si iluminator infrarosu Necesita alimentator.	<b>175 lei</b>
	<b>MC-D507SN</b>	Camera de supraveghere video color de tip dom; Senzor <b>1/4" Sharp color CCD</b> Rezolutie <b>420TVL</b> ; Iluminare minima 0,2 Lux; <b>lentila 3,5 - 8 mm cu iris manual (74-32 grade)</b> ; Procesor DSP Sharp; Nivel semnal/zgomot >48db; Tensiune de alimentare 12V cc; Consum maxim 250 mA; Include lentila. Necesita alimentator.	<b>175 lei</b>
	<b>MC-D507F</b>	Camera de supraveghere video color de tip dom; Senzor <b>1/3" Sony SUPER HAD CCD</b> ; Rezolutie <b>420TVL</b> , Iluminare minima 0,1 LUX <b>lentila 3,5 - 8 mm cu iris manual (74-32 grade)</b> ; Procesor DSP Sony; Nivel semnal/zgomot >48db; Tensiune de alimentare 12V cc; Consum maxim 250 mA; Include lentila. Necesita alimentator.	<b>215 lei</b>
<b>Camere de tip box</b>			
	<b>MC-B354F</b>	Camera de supraveghere video color de tip box; Senzor <b>1/4" Sharp color CCD</b> Rezolutie <b>420TVL</b> ; Iluminare minima 0,8 Lux F 1.2; Procesor DSP Sharp; Nivel semnal/zgomot >48db; Tensiune de alimentare 12V cc; Consum maxim 150 mA; <b>Include microfon 1.0V p-p 600 ohm</b> . Necesita alimentator, lentila si suport. Alimentare cu prindere pe console cu surub.	<b>115 lei</b>

	<b>MC-B354SN</b>	Camera de supraveghere video color de tip box; Senzor <b>1/3" Sony SUPER HAD CCD</b> ; Rezolutie <b>420TVL</b> , Iluminare minima 0,5 LUX F 1.2 Procesor DSP Sony; Nivel semnal/zgomot >48db;Tensiune de alimentare 12V cc; Consum maxim 150 mA; <b>Include microfon 1.0V p-p 600 ohm</b> .Necesita alimentator, lentila si suport. Alimentare cu prindere pe console cu surub.	<b>165 lei</b>
	<b>MC-B500F</b>	Camera de supraveghere video color de tip box day/night; Senzor <b>1/4" Sharp color CCD</b> Rezolutie <b>420TVL</b> ; Iluminare minima 0.1LuxF1.2 mod color 0.01Lux F1.2(B&W); Procesor DSP Sharp; Nivel semnal/zgomot >48db;Tensiune de alimentare 12V cc; Consum maxim 150 mA; Necesita alimentator, lentila si suport.	<b>145 lei</b>
	<b>MC-B500SN</b>	Camera de supraveghere video color de tip box; Senzor <b>1/3" Sony SUPER HAD CCD</b> ; Rezolutie <b>420TVL</b> , Iluminare minima 0.1LuxF1.2 mod color 0.01Lux F1.2(B&W); Procesor DSP Sony; Nivel semnal/zgomot >48db;Tensiune de alimentare 12V cc; Consum maxim 150 mA;Necesita alimentator, lentila si suport.	<b>190 lei</b>
	<b>MC-B20S</b>	Camera de supraveghere video color de tip box de inalta definitie; Senzor <b>1/4" Sony ExView CCD</b> ; Rezolutie <b>420TVL</b> , Iluminare minima 0.2LuxF1.2 mod color; Procesor DSP Sony; Nivel semnal/zgomot >48db;Tensiune de alimentare <b>220V AC</b> ; Consum maxim 150 mA;Necesita lentila si suport.	<b>210 lei</b>
	<b>MC-B20SNH</b>	Camera de supraveghere video color de tip box de inalta definitie; Senzor <b>1/3" Sony ExView CCD</b> ; Rezolutie <b>480TVL</b> , Iluminare minima 0.02LuxF1.2 mod color; Procesor DSP Sony; <b>Funcctie Starlight</b> ; Nivel semnal/zgomot >48db;Tensiune de alimentare <b>220V AC</b> ; Consum maxim 150 mA; Necesita lentila si suport.	<b>270 lei</b>
	<b>MC-B20SNH-2</b>	Camera de supraveghere video color de tip box de inalta definitie; Senzor <b>1/3" Sony ExView CCD</b> ; Rezolutie <b>540TVL</b> , Iluminare minima 0.02LuxF1.2 mod color; Procesor DSP Sony; <b>Funcctie Starlight</b> ; Nivel semnal/zgomot >48db;Tensiune de alimentare 12V cc; Consum maxim 150 mA; Necesita lentila, alimentator si suport.	<b>295 lei</b>
	<b>MC-B352</b>	Camera de supraveghere video color de tip box; Senzor <b>1/3" Sony SUPER HAD CCD</b> ; Rezolutie <b>420TVL</b> , Iluminare minima 0,8 LUX F 1.2 Procesor DSP Sony; Nivel semnal/zgomot >48db;Tensiune de alimentare 12V cc; Consum maxim 150 mA; <b>Include lentila varifocala iris manual 3,5 - 8 mm. Reglaje OSD (on screen display)</b> ; Necesita alimentator si suport. Alimentare cu prindere pe console cu surub.	<b>275 lei</b>

	<b>MC-B347SNH</b>	Camera de supraveghere video color de tip box; Senzor <b>1/3" Sony SUPER HAD CCD</b> ; Rezolutie <b>480TVL</b> , Iluminare minima 0,8 LUX F 1.2 Procesor DSP Sony; Nivel semnal/zgomot >48db;Tensiune de alimentare 12V cc; Consum maxim 150 mA; <b>Include lentila varifocala iris manual 3,5 - 8 mm</b> ; Necesita alimentator si suport.	<b>270 lei</b>
<b>Camere pentru interior/medii ostile cu IR</b>			
	<b>MC-121F</b>	Camera de supraveghere video color DAY/NIGHT; Senzor <b>1/4" Sharp color CCD</b> Rezolutie <b>420TVL</b> ; Iluminare minima 0 LUX (IR pornit); <b>Lentila 3.6 mm (63 grade)</b> ; Illuminator <b>18 leduri IR</b> - distanta iluminata pe timp de noapte maxim 15 m; Procesor DSP Sharp; Nivel semnal/zgomot >48db;Tensiune de alimentare 12V cc; Consum maxim 400 mA; Include lentila ,suport si iluminator infrarosu. Necesita alimentator.	<b>135 lei</b>
	<b>MC-W67F</b>	Camera de supraveghere video color DAY/NIGHT; Senzor <b>1/4" Sharp color CCD</b> Rezolutie <b>420TVL</b> ; Iluminare minima 0 LUX (IR pornit) <b>lentila 3.6 mm (63 grade)</b> ; Illuminator <b>24 leduri IR</b> - distanta iluminata pe timp de noapte maxim 18 m; Procesor DSP Sharp; Nivel semnal/zgomot >48db;Tensiune de alimentare 12V cc; Consum maxim 400 mA; Include lentila, suport, si iluminator infrarosu; Necesita alimentator. <b>Factor de protectie IP 57;</b>	<b>150 lei</b>
	<b>MC-W119F</b>	Camera de supraveghere video color DAY/NIGHT; Senzor <b>1/4" Sharp color CCD</b> Rezolutie <b>420TVL</b> ; Iluminare minima 0 LUX (IR pornit) <b>lentila 3.6 mm (63 grade)</b> ; Illuminator <b>30 leduri IR</b> - distanta iluminata pe timp de noapte maxim 25 m; Procesor DSP Sharp; Nivel semnal/zgomot >48db;Tensiune de alimentare 12V cc; Consum maxim 400 mA; Include lentila, suport si iluminator infrarosu. Necesita alimentator.	<b>160 lei</b>
	<b>MC-W67SN</b>	Camera de supraveghere video color DAY/NIGHT; Senzor <b>1/3" Sony SUPER HAD CCD</b> ; Rezolutie <b>420TVL</b> , Iluminare minima 0 LUX (IR pornit) <b>lentila 3.6 mm (74 grade)</b> ; Illuminator <b>24 leduri IR</b> , distanta iluminata pe timp de noapte maxim 20 m. Procesor DSP Sony; Nivel semnal/zgomot >48db;Tensiune de alimentare 12V cc; Consum maxim 400 mA; Include lentila, suport si iluminator infrarosu. Factor de protectie IP 57. Necesita alimentator.	<b>180 lei</b>
	<b>MC-W119SN</b>	Camera de supraveghere video color DAY/NIGHT; Senzor <b>1/3" Sony SUPER HAD CCD</b> ; Rezolutie <b>420TVL</b> , Iluminare minima 0 LUX (IR pornit) <b>lentila 3.6 mm (74 grade)</b> ; Illuminator <b>30 leduri IR</b> , distanta iluminata pe timp de noapte maxim 30 m. Procesor DSP Sony; Nivel semnal/zgomot >48db;Tensiune de alimentare 12V cc; Consum maxim 400 mA; Include lentila, suport si iluminator infrarosu. Necesita alimentator.	<b>185 lei</b>

Camere pentru exterior cu IR



	<p><b>MC-W124SN</b></p>	<p>Camera de supraveghere video color de exterior DAY/NIGHT; Senzor <b>1/3" Sony SUPER HAD CCD</b>; Rezolutie <b>420TVL</b>, Iluminare minima 0 LUX (IR pornit) <b>lentila 3.6 mm (74 grade)</b>; Iluminator <b>48 leduri IR</b>, distanta iluminata pe timp de noapte maxim 45 m. Procesor DSP Sony; Nivel semnal/zgomot &gt;48db;Tensiune de alimentare 12V cc; Consum maxim 700 mA; Include lentila, carcasa de exterior, suport si iluminator infrarosu. Optional lentila 6, 8, 12 sau 16 mm (schimbarea lentilei nu implica costuri suplimentare). Necesita alimentator.</p>	<p><b>230 lei</b></p>
	<p><b>MC-W124F</b></p>	<p>Camera de supraveghere video color de exterior DAY/NIGHT; Senzor <b>1/4" Sharp color CCD</b> Rezolutie <b>420TVL</b>; Iluminare minima 0 LUX (IR pornit) <b>lentila 3.6 mm( 63 grade)</b>; Iluminator <b>48 leduri IR</b> - distanta iluminata pe timp de noapte maxim 40 m; Procesor DSP Sharp;Nivel semnal/zgomot &gt;48db;Tensiune de alimentare 12V cc; Consum maxim 700 mA; Include lentila, carcasa de exterior, suport si iluminator infrarosu. Optional lentila 6, 8, 12 sau 16 mm (schimbarea lentilei nu implica costuri suplimentare) Necesita alimentator.</p>	<p><b>165 lei</b></p>
	<p><b>MC-W12SN</b></p>	<p>Camera de supraveghere video color de exterior DAY/NIGHT; Senzor <b>1/3" Sony SUPER HAD CCD</b>; Rezolutie <b>420TVL</b>, Iluminare minima 0 LUX (IR pornit) <b>lentila 3.6 mm (74 grade)</b>; Iluminator <b>48 leduri IR</b>, distanta iluminata pe timp de noapte maxim 45 m. Procesor DSP Sony; Nivel semnal/zgomot &gt;48db;Tensiune de alimentare 12V cc; Consum maxim 700 mA; Include lentila, carcasa de exterior, suport cu posibilitate de fixare pe tavan sau perete si iluminator infrarosu. Optional lentila 6, 8, 12 sau 16 mm (schimbarea lentilei nu implica costuri suplimentare). Necesita alimentator.</p>	<p><b>245 lei</b></p>
	<p><b>MC-W12F</b></p>	<p>Camera de supraveghere video color de exterior DAY/NIGHT; Senzor <b>1/4" Sharp color CCD</b> Rezolutie <b>420TVL</b>; Iluminare minima 0 LUX (IR pornit) <b>lentila 3.6 mm( 63 grade)</b>; Iluminator <b>48 leduri IR</b> - distanta iluminata pe timp de noapte maxim 40 m; Procesor DSP Sharp;Nivel semnal/zgomot &gt;48db;Tensiune de alimentare 12V cc; Consum maxim 700 mA; Include lentila, carcasa de exterior si iluminator infrarosu. Optional lentila 6, 8, 12 sau 16 mm (schimbarea lentilei nu implica costuri suplimentare) Necesita alimentator.</p>	<p><b>175 lei</b></p>
	<p><b>MC-W106SN</b></p>	<p>Camera de supraveghere video color de exterior DAY/NIGHT; Senzor <b>1/3" Sony SUPER HAD CCD</b>; Rezolutie <b>420TVL</b>, Iluminare minima 0 LUX (IR pornit) <b>lentila 6 mm (44 grade)</b>; Iluminator <b>104 leduri IR</b>, distanta iluminata pe timp de noapte maxim 80 m. Procesor DSP Sony; Nivel semnal/zgomot &gt;48db;Tensiune de alimentare 12V cc; Consum maxim 900 mA; Include lentila, carcasa de exterior, si iluminator infrarosu. Necesita alimentator si suport.</p>	<p><b>350 lei</b></p>

	<p><b>MC-W106F</b></p>	<p>Camera de supraveghere video color de exterior DAY/NIGHT; Senzor <b>1/4" Sharp color CCD</b> Rezolutie <b>420TVL</b>; Iluminare minima 0 LUX (IR pornit) <b>lentila 6 mm(33 grade)</b>; Illuminator <b>104 leduri IR</b> - distanta iluminata pe timp de noapte maxim 70 m; Procesor DSP Sharp; Nivel semnal/zgomot &gt;48db; Tensiune de alimentare 12V cc; Consum maxim 900 mA; Include lentila, carcasa de exterior, si iluminator infrarosu. Necesita alimentator si suport.</p>	<p><b>275 lei</b></p>
	<p><b>MC-W513SNH</b></p>	<p>Camera de supraveghere video color de exterior high res DAY/NIGHT; Senzor <b>1/3" Sony SUPER HAD CCD</b>; Rezolutie <b>480TVL</b>, Iluminare minima 0 LUX (IR pornit) <b>lentila 3,5 - 8 mm cu iris manual (74-32 grade)</b>; Illuminator <b>48 leduri IR</b>, distanta iluminata pe timp de noapte maxim 40 m. Procesor DSP Sony 10 bit; Nivel semnal/zgomot &gt;48db; Tensiune de alimentare 12V cc; Consum maxim 700 mA; Include lentila, carcasa de exterior, suport cu sistem antitaiere cablu si iluminator infrarosu. Necesita alimentator <b>Factor de protectie IP 65</b>.</p>	<p><b>370 lei</b></p>
 <p>With OSD</p>	<p><b>MC-W55SNH-2A</b></p>	<p>Camera de supraveghere video color de exterior DAY/NIGHT; Senzor <b>1/3" Sony SUPER HAD CCD</b>; Rezolutie <b>540TVL</b>, Iluminare minima 0 LUX (IR pornit) <b>lentila varifocala cu iris manual 4 - 9 mm (67-28 grade)</b>; Illuminator <b>48 leduri IR</b>, distanta iluminata pe timp de noapte maxim 50 m. Procesor DSP Sony 10 bit; <b>Reglaje OSD (on screen display)</b>; Nivel semnal/zgomot &gt;48db; Tensiune de alimentare 12V cc; Consum maxim 700 mA; Include lentila, carcasa de exterior, suport cu sistem antitaiere cabluri si iluminator infrarosu. Necesita alimentator</p>	<p><b>400 lei</b></p>
 <p>With OSD</p>	<p><b>MC-W55SNA</b></p>	<p>Camera de supraveghere video color de exterior DAY/NIGHT; Senzor <b>1/3" Sony SUPER HAD CCD</b>; Rezolutie <b>480TVL</b>, Iluminare minima 0 LUX (IR pornit) <b>lentila varifocala cu iris manual 4 - 9 mm (67 - 28 grade)</b>; Illuminator <b>48 leduri IR</b>, distanta iluminata pe timp de noapte maxim 50 m. Procesor DSP Sony 10 bit; <b>Reglaje OSD (on screen display)</b>; Nivel semnal/zgomot &gt;48db; Tensiune de alimentare 12V cc; Consum maxim 700 mA; Include lentila, carcasa de exterior, suport cu sistem antitaiere cabluri si iluminator infrarosu. Necesita alimentator</p>	<p><b>345 lei</b></p>

	<b>MC-W1151</b>	Camera de supraveghere video color de exterior DAY/NIGHT; Senzor <b>1/3" Sony SUPER HAD CCD</b> ; Rezolutie <b>480TVL</b> , Iluminare minima 0 LUX (IR pornit) <b>lentila 3.6 mm (74 grade)</b> ; Iluminator <b>30 leduri IR</b> , distanta iluminata pe timp de noapte maxim 30 m. Procesor DSP Sony; Nivel semnal/zgomot >48db;Tensiune de alimentare 12V cc; Include lentila, carcasa de exterior si iluminator infrarosu. Optional lentila 6, 8, 12 sau 16 mm (schimbarea lentilei nu implica costuri suplimentare). Necesita alimentator si suport.	<b>230 lei</b>
<b>Camere miniaturizate/ascunse</b>			
	<b>MC 201</b>	Camera de supraveghere video color.Camera mascata in detector de fum nefunctional. Element imagine: 1/3 SHARP CCD. Rezolutie efectiva: 512x582 pixeli. Definitie orizontala: 420 linii TV. Unghi vizual 76o. Iluminare minima:0.5 Lux/F1.2. Tensiune de alimentare 12Vcc. Nivel semnal video: 1.0Vp-p/75W. Contine lentila de 3,6mm.	<b>187 lei</b>
	<b>MC 901</b>	Camera de supraveghere video color.Camera mascata in senzor de miscare PIR nefunctional. Element imagine: ¼ SHARP CCD. Rezolutie efectiva: 512x582 pixeli. Definitie orizontala: 420 linii TV. Unghi vizual 76o. Iluminare minima: 1Lux/F1.2. Tensiune de alimentare: 12Vcc. Nivel semnal video: 1.0Vp-p/75W. Contine lentila de 3,6mm.	<b>187 lei</b>
	<b>MC 280</b>	Camera de supraveghere video color tip bullet. Element imagine: SHARP CCD. Rezolutie efectiva: 512x582 pixeli. Definitie orizontala: 420 linii TV. Unghi vizual 76o. Iluminare minima: 0,8Lux/F1.2. Tensiune de alimentare: 12Vcc. Nivel semnal video: 1.0Vp-p/75W. Contine lentila de 3,6mm si suport metalic.	<b>200 lei</b>
<b>Camere IP</b>			
	<b>IP DOME</b>	Speed dome IP de exterior. Glob de 6", carcasa din aluminiu, zgomot redus, viteza pan max. 15/s, viteza tild max. 15/s, 64 de pozitii presetate, 6 trasee fiecare cu cate 16 pozitii presetate, alimentare 24Vca, consum 20VA, are incalzitor si ventilator, cursa pan 360° continuu, cursa tild 90° (180° cu autorotire), temperatura de lucru -35°C ~ +55°C, greutate 4Kg. Camera: SONY fabricata in Japonia cu zoom optic 18X (f=4,1~73,8mm), day/night cu filtru mecanic retractabil automat, rezolutie orizontala 480 de linii TV, focus automat, iluminare minima 0,01 Lux, compresie MPEG4, rezolutie maxima 2CIF 640x480, 25fps, banda utilizata 100Kbps-1Mbps. <b>Se livreaza cu suport de perete, suport de tavan si alimentator.</b>	<b>3,454 lei</b>
	<b>ACM-4100</b>	MPEG-4 Indoor IP Cube Camera supports VGA resolution @ 25fps / two-way audio, Micron Super CMOS module, f4.2mm/F1.8 lens, DC3.3V, Power Adapter, bracket, ACTi Streaming Activator S/W <b>Garantie 24 de luni!!</b>	<b>732 lei</b>
	<b>ACM-4200</b>	Low-Cost MPEG-4 <b>MegaPixel</b> Indoor IP <b>Cube</b> Camera supports up to <b>1.3MegaPixel</b> resolution w/ two-way audio, Micron MegaPixel CMOS module, CS Mount, f4.2mm/F1.8 lens, <b>DC3.3V</b> , Power Adapter, ACTi Streaming Activator S/W	<b>965 lei</b>

	<b>ACM-1311P</b>	Entry-level MPEG-4 <b>Indoor IR</b> IP Bullet Camera supports up to Full D1 resolution, w/ <b>two-way audio</b> , <b>420 TV line</b> <b>Sony SuperHAD CCD</b> Module, <b>f4.3mm/ F2.0</b> , <b>PoE</b> , Power Adapter, ACTi Streaming Activator S/W	1,381 lei
	<b>ACM-1431P</b>	Entry-level MPEG-4 <b>Outdoor IR Day and Night</b> IP Bullet Camera supports up to Full D1 resolution, w/ <b>two-way audio</b> , <b>540 TV line</b> <b>Sony SuperHAD CCD</b> module, <b>f3.8 ~ 9.5mm/ F1.2</b> , <b>PoE</b> , Power Adapter, ACTi Streaming Activator S/W, <b>IP-66</b>	2,058 lei
	<b>ACM-1432P</b>	Entry-level MPEG-4 <b>Outdoor IR Day and Night</b> IP Bullet Camera supports up to Full D1 resolution, w/ <b>two-way audio</b> <b>540 TV line</b> , <b>Sony SuperHAD CCD</b> module, <b>f3.8 ~ 9.5mm/ F1.2</b> , <b>AC24V</b> , Power Adapter (DC12V), ACTi Streaming Activator S/W, <b>IP-66</b>	2,058 lei
	<b>ACM-3211N/P</b>	MPEG-4 Indoor IR IP Dome Camera supports up to Full D1 resolution, w/ <b>two-way audio</b> , <b>420 TV line</b> , <b>Sony SuperHAD CCD</b> Module, <b>f4.3mm/ F2.0</b> , <b>PoE</b> , Power Adapter, ACTi Streaming Activator S/W <b>Garantie 24 de luni!!</b>	1,473 lei
	<b>ACM-3311N/P</b>	MPEG-4 Indoor IR IP 3" Dome Camera supports up to Full D1 resolution, w/ <b>two-way audio</b> , <b>420 TV line</b> , <b>Sony SuperHAD CCD</b> Module, <b>f4.3mm/ F2.0</b> , <b>PoE</b> , Power Adapter, ACTi Streaming Activator S/W <b>Garantie 24 de luni!!</b>	1,217 lei
	<b>CAM-5201P</b>	MPEG-4 PAL IP Camera supports up to Full D1 resolution, w/ <b>one-way audio</b> , <b>480 TV line</b> , <b>Sony SuperHAD</b> CCD module, <b>PoE</b> , Power Adapter, ACTi Streaming Activator S/W	2,000 lei
	<b>CAM-5221P</b>	MPEG-4 PAL <b>Day and Night</b> IP Camera supports up to Full D1 resolution, w/ <b>one-way audio</b> , <b>480 TV line</b> , <b>Sony Exview</b> CCD module, <b>PoE</b> , Power Adapter, ACTi Streaming Activator S/W	2,459 lei
	<b>CAM-5301P</b>	MPEG-4 PAL IP Camera supports up to Full D1 resolution, w/ <b>480 TV line</b> , <b>Sony SuperHAD</b> CCD module, <b>PoE</b> , Power Adapter, ACTi Streaming Activator S/W	1,870 lei
	<b>CAM-5321P</b>	MPEG-4 PAL <b>Day and Night</b> IP Camera supports up to Full D1 resolution, w/ <b>480 TV line</b> , <b>Sony Exview</b> CCD module, <b>PoE</b> , Power Adapter, ACTi Streaming Activator S/W	2,300 lei
	<b>CAM-5322P</b>	MPEG-4 PAL <b>Day and Night</b> IP Camera supports up to Full D1 resolution, w/ <b>480 TV line</b> , <b>Sony Exview</b> CCD module, <b>AC24V</b> , Power Adapter (DC12V), ACTi Streaming Activator S/W	2,451 lei
	<b>ACM-5001</b>	M-JPEG/MPEG-4 <b>VGA</b> IP Camera supports up to <b>VGA</b> resolution w/ <b>two-way audio</b> , <b>Micron MegaPixel CMOS</b> module, <b>CS Mount</b> , bundled <b>f4.2mm/F1.8 lens</b> , <b>PoE</b> , Power Adapter, ACTi NVR S/W	1,310 lei
	<b>ACM-5711P</b>	Entry-Level MPEG-4 PAL IP Camera supports up to Full D1 resolution, w/ <b>two-way audio</b> , <b>420 TV line</b> , <b>Sony SuperHAD</b> CCD module, <b>PoE</b> , Power Adapter, ACTi Streaming Activator S/W	1,490 lei
	<b>ACM-5601</b>	MPEG-4 <b>MegaPixel</b> IP Camera supports up to <b>1.3MegaPixel</b> resolution w/ <b>two-way audio</b> , <b>Micron MegaPixel CMOS</b> module, <b>CS Mount</b> , bundled <b>f4.2mm/F1.8 lens</b> , <b>PoE</b> , Power Adapter, ACTi Streaming Activator S/W	1,400 lei


	<b>ACM-5611</b>	MPEG-4 <b>MegaPixelDay and Night</b> IP Camera supports up to <b>1.3MegaPixel</b> resolution w/ two-way audio, Micron MegaPixel CMOS module, CS Mount, bundled f4.2mm/F1.8 lens, <b>PoE</b> , Power Adapter, ACTi Streaming Activator S/W	1,700 lei
	<b>ACD-2100</b>	MPEG-4 Video Server supports up to Full D1 resolution, w/ two-way audio, Power Adapter, ACTi Streaming Activator S/W Garantie 24 de luni!!	1,143 lei
	<b>SED-2120</b>	MPEG-4 Video Server supports up to Full D1 resolution, w/ Power Adapter, ACTi Streaming Activator S/W Garantie 24 de luni!!	1,648 lei
	<b>SED-2140T</b>	MPEG-4 Video Server supports up to Full D1 resolution, w/ two-way audio, Power Adapter, ACTi Streaming Activator S/W, Extended temperature Garantie 24 de luni!!	2,435 lei
	<b>SED-2320Q</b>	MPEG-4 Quad Processor Integrated Video Server, supports up to Full D1 resolution, w/ two-way audio, Power Adapter, ACTi Streaming Activator S/W Garantie 24 de luni!!	1,957 lei
	<b>SED-2420</b>	2-channel MPEG-4 Video Server supports up to Full D1 resolution, w/ two-way audio, Power Adapter, BNC connectors, ACTi Streaming Activator S/W Garantie 24 de luni!!	2,435 lei
	<b>ACD-2200</b>	4-channel MPEG-4 Video Server supports up to Full D1 resolution, w/ two-way audio, Power Adapter, BNC connectors, ACTi Streaming Activator S/W Garantie 24 de luni!!	3,811 lei
	<b>SED-2610</b>	8-channel MPEG-4 Video Server supports up to Full D1 resolution, w/ two-way audio, Power Supply, ACTi Streaming Activator S/W Garantie 24 de luni!!	11,339 lei
	<b>SED-3300</b>	MPEG-4 Transcoder supports up to full D1 video resolution for regular TV system and digital TV, w/ Power Adapter Garantie 24 de luni!!	1,648 lei
	<b>ACD-3100</b>	Entry-Level MPEG-4 Video Decoder supports up to full D1 video resolution for regular TV system and digital TV, w/ <b>two-way audio</b> , Power Adapter	1,200 lei
	<b>SED-3320</b>	MPEG-4 Transcoder supports up to full D1 video resolution for regular TV system and digital TV, w/ two-way audio, Power Adapter Garantie 24 de luni!!	1,957 lei
	<b>APP-2000-16</b>	Network Video Recorder S/W, supports 16 channels	<b>PROMO GRATUIT</b>
	<b>APP-2000-32</b>	Network Video Recorder S/W, supports 32 channels	4,573 lei
	<b>APP-2000-48</b>	Network Video Recorder S/W, supports 48 channels	7,317 lei
	<b>APP-2000-64</b>	Network Video Recorder S/W, supports 64 channels	9,604 lei
	<b>RMK-2000</b>	4U Rackmount Kit for Wall-mount type devices, for all video servers and transcoders except SED-2100R, w/ 8 front bezel	2,377 lei
	<b>R306-00003-000</b>	Front bezel for 2-ch video server, for RMK-2000	58 lei

	<b>R306-0004-000</b>	Front bezel for 1-ch video server and transcoder, for RMK-2000	58 lei
	<b>R306-0006-000</b>	Front bezel for 1-ch NB2, for RMK-2000	58 lei
	<b>R306-0007-000</b>	Blank front bezel for RMK-2000	58 lei
<b>Camere Speed Dome</b>			
	<b>MC 420 IN</b>	Mini speed dome de interior. Glob de 3,5", viteza pan max. 12s, viteza tild max. 12/s, 32 de pozitii presetate, multiprotocol, comunicatie RS485, alimentare 12Vcc, consum 12VA, cursa pan 360° continuu, cursa tild 90°, temperatura de lucru -10°C ~ +50°C, greutate 1Kg. Camera: SONY CCD 1/3", pixeli activi 512(H)x582(V), rezolutie orizontala 420 de linii TV, lentila fixa, AGC, BLC, AWB, iluminare minima 0,5 Lux.	754 lei
	<b>MC 420 VP OUT</b>	Mini speed dome de exterior antivandal. Glob de 3,5", carcasa de aluminiu, viteza pan max. 12/s, viteza tild max. 12/s, 32 de pozitii presetate, multiprotocol, comunicatie RS485, alimentare 12Vcc, consum 12VA, cursa pan 360° continuu, cursa tild 90°, temperatura de lucru -20°C ~ +55°C, greutate 1Kg. Camera: SONY CCD 1/3", pixeli activi 512(H)x582(V), rezolutie orizontala 420 de linii TV, lentila autoiris, AGC, BLC, AWB, iluminare minima 0,5 Lux.	824 lei
	<b>SK 07</b>	Speed dome de exterior/interior. Glob de 7", carcasa din plastic, zgomot redus, viteza pan max. 12/s, viteza tild max. 12/s, multiprotocol, comunicatie RS485, alimentare 24Vca, consum 30VA, are incalzitor si ventilator, cursa pan 355, cursa tild 90°, temperatura de lucru -35°C~+55°C, greutate 3Kg. Camera: CCD 1/3 SONY PAL cu zoom optic 22X (f=5~85mm), day/night, rezolutie orizontala 420 de linii TV, focus manual, iluminare minima 0,1 Lux. <i>Se livreaza cu suport de perete, suport de tavan si alimentator.</i>	1,487 lei
	<b>SK 06 IN</b>	Speed dome de interior. Viteza pan max. 15s, viteza tild max. 15/s, 64 de pozitii presetate, 6 trasee fiecare cu cate 16 pozitii presetate, multiprotocol, comunicatie RS485, alimentare 12Vcc, consum 20VA, cursa pan 360° continuu, cursa tild 90°, temperatura de lucru -10°C ~ +50°C, greutate 2Kg. Camera: LG fabricata in Korea cu zoom 27X (f=3.6~98mm), day/night, pixeli activi 795(H)x596(V), rezolutie orizontala 480 de linii TV, focus automat, iluminare minima 0,01 Lux.	2,034 lei






	<b>DK 06 OUT</b>	Speed dome de exterior. Glob de 6", carcasa din aluminiu, zgomot redus, viteza pan max. 15 o/s, viteza tild max. 15 o/s, 64 de pozitii presetate, 6 trasee fiecare cu cate 16 pozitii presetate, multiprotocol, comunicatie RS485, alimentare 24Vca, consum 20VA, are incalzitor si ventilator, cursa pan 360o continuu, cursa tild 90o (180o cu autorotire), temperatura de lucru -45oC ~ +55oC, greutate 4Kg. Camera: LG fabricata in Korea cu zoom 27X (f=3.6~98mm), day/night, pixeli activi 795(H)x596(V), rezolutie orizontala 480 de linii TV, focus automat, iluminare minima 0,01 Lux. Se livreaza cu suport de perete, suport de tavan si alimentator.	2,174 lei
	<b>MC 270 OUT</b>	Speed dome de exterior. Glob de 6", carcasa din aluminiu, zgomot redus, viteza pan max. 80o/s, viteza tild max. 40o/s, 64 de pozitii presetate, 6 trasee fiecare cu cate 16 pozitii presetate, multiprotocol, comunicatie RS485, alimentare 24Vca, consum 20VA, are incalzitor si ventilator, cursa pan 360o continuu, cursa tild 90o (180o cu autorotire), temperatura de lucru -45oC ~ +55oC, greutate 4Kg. Camera: LG fabricata in Korea cu zoom 27X (f=3.6~98mm), day/night, pixeli activi 795(H)x596(V), rezolutie orizontala 480 de linii TV, focus automat, iluminare minima 0,01 Lux. Se livreaza cu suport de perete, suport de tavan si alimentator.	2,770 lei
	<b>GLBF</b>	<b>Glob fumuriu pentru speed dome.</b>	123 lei
	<b>KB101</b>	Tastatura de comanda multiprotocol cu afisaj LCD; poate accesa maxim 32 de speed domuri; se poate comanda pan, tild, zoom, focus, iris si alti parametrii; puncte si trasee presetate, autotur, autoscan; protocol de comunicatie RS485.	964 lei
	<b>KB102</b>	Tastatura de comanda multiprotocol; poate accesa maxim 32 de speed domuri; se poate comanda pan, tild, zoom, focus, iris si alti parametrii; puncte si trasee presetate, autotur, autoscan; protocol de comunicatie RS485.	421 lei
	<b>RS485</b>	Convertor RS232-RS485	123 lei
<b>Accesorii</b>			
	<b>202E</b>	Transmitator miniatura pasiv maxim 400m color si 600m alb/negru. Se foloseste pereche cu 202C.	18 lei
	<b>202C</b>	Receptor miniatura pasiv maxim 400m color si 600m alb/negru. Se foloseste pereche cu 202E.	18 lei
	<b>611</b>	Transmitator pasiv maxim 400m color si 600m alb/negru. Se foloseste pereche cu 611B.	25 lei

	<b>611B</b>	Receptor pasiv maxim 400m color si 600m alb/negru. Se foloseste pereche cu 611.	25 lei
	<b>2401T</b>	Transmitator activ; 1 canal video; Distanța de transmisie: 2400 m-color; 3000 m alb/negru	105 lei
	<b>2401R</b>	Receptor activ; 1 canal video; Distanța de transmisie: 2400 m-color; 3000 m alb/negru	105 lei
	<b>2404T</b>	Transmitator activ; 4 canale video; Distanța de transmisie: 2400 m-color; 3000 m alb/negru	228 lei
	<b>2404R</b>	Receptor activ; 4 canale video; Distanța de transmisie: 2400 m-color; 3000 m alb/negru	228 lei
	<b>2416R</b>	Receptor activ; 16 canale video; Distanța de transmisie: 2400 m-color; 3000 m alb/negru	579 lei
	<b>CCE 01</b>	Carcasa exteriora din aluminiu fara climatizare	55 lei
	<b>FD-801H</b>	Carcasa de exterior termostata cu incalzitor	75 lei
	<b>FD-801HB</b>	Carcasa de exterior termostata cu incalzitor si ventilator	85 lei
	<b>B07</b>	Suport metalic de dimensiune medie vopsit electrostatic	17 lei
	<b>B06</b>	Suport inox de dimensiune medie vopsit electrostatic	18 lei
	<b>B08</b>	Suport metalic 360 dubla articulatie	18 lei
	<b>A01HB</b>	Suport din plastic negru	11 lei

	<b>A01HW</b>	Suport din plastic alb	11 lei
	<b>BR12</b>	Suport metalic lung vopsite electrostatic	25 lei
	<b>12V1A</b>	Alimentator in comutatie 12V - 1000 mA	18 lei
	<b>12V4A</b>	Alimentator in comutatie 12V - 4000 mA	60 lei
	<b>12V2A</b>	Alimentator in comutatie 12V - 2000 mA	35 lei
	<b>MBNC</b>	Mufe BNC cu sertizare mecanica prin infiletare	3 lei
	<b>RG 60</b>	Cablu coaxial RG 60@75 Ohm - role 100m	50 lei
	<b>2X0.75</b>	Cablu alimentare 2 x 0.75 - role 100m	70 lei
<b>Lentile</b>			
	<b>LCS 01</b>	Lentile mici de tip board /dome: Distanta focala: 3,6 mm. Unghi vizual: 80o. Distanta focala: 4,3 mm. Unghi vizual: 65o. Distanta focala: 6 mm cu filtru IR. Unghi vizual: 53o. Distanta focala: 6 mm. Unghi vizual: 53o. Distanta focala: 16 mm. Unghi vizual: 21o. (pretul este /bucata)	17 lei
	<b>LCS 02</b>	Lentile mici de tip board /dome: Distanta focala: 2,8 mm. Unghi vizual: 94o. (pretul este /bucata)	28 lei
	<b>LCS 03</b>	Lentile fixe: Distanta focala: 4 mm. Unghi vizual: 74o. Distanta focala: 6 mm. Unghi vizual: 53o. Distanta focala: 12 mm. Unghi vizual: 28o. Distanta focala: 16 mm. Unghi vizual: 21o. (pretul este /bucata)	17 lei
	<b>LCS 04</b>	Lentile fixe: Distanta focala: 2,8 mm. Unghi vizual: 94o. (pretul este /bucata)	28 lei
	<b>LCS 05</b>	Lentila varifocala cu iris manual.Distanta focala reglabila: 3.5-8 mm. Unghi vizual: 81o-41o	40 lei
	<b>LCS 06</b>	Lentila varifocala cu iris manual.Distanta focala reglabila: 6-15 mm. Unghi vizual: 53o-22o	50 lei

	<b>LCS 07</b>	Lentila varifocala cu auto iris.Distanta focala reglabila: 3,5-8 mm. Unghi vizual: 81o-41o	84 lei
	<b>LCS 08</b>	Lentila varifocala cu auto irisDistanta focala reglabila: 6-15 mm. Unghi vizual: 53o-22o	91 lei
<b>Placi de captura Wave P</b>			
	<b>EH10104</b>	Placa DVR 4 canale video, 50 fps, rezolutie 640x480, compresie H.264 (MPEG 4/part10), detectie miASare, control prin LAN, control PTZ, sistem operare WIN 2000/XP, cerinte minime PC: P4 1,7GHz, 256 MB, video ATI 64MB Maxim 4 placi intr-un PC (16 canale). Imagine fara efect "interlace".Garantie 24 luni.	150 lei
	<b>EH10416</b>	Placa DVR 16 canale video, 200 fps, rezolutie 640x480, compresie H.264 (MPEG 4/part10), detectie miASare, control prin LAN, control PTZ, sistem operare WIN 2000/XP, cerinte minime PC: P4 1,7GHz, 256 MB, video ATI 64MB Maxim 2 placi intr-un PC (32 canale). Imagine fara efect "interlace".	515 lei
	<b>EH9404</b>	Placa DVR 4 canale video, 9 bit PHILIPS ADC, 100 fps, rezolutie 640x480, compresie H.264 (MPEG 4/part10), detectie miASare, control prin LAN, control PTZ, sistem operare WIN 2000/XP, cerinte minime PC: P4 1,7GHz, 256 MB, video 64MB. Maxim 4 placi intr-un PC (16 canale). Calitate excelenta a imaginii !!	402 lei
	<b>EH9404A</b>	Placa DVR 4 canale video, 4 canale audio, 9 bit PHILIPS ADC, 100 fps, rezolutie 640x480, compresie H.264 (MPEG 4/part10), detectie miASare, control prin LAN, control PTZ, sistem operare WIN 2000/XP, cerinte minime PC: P4 1,7GHz, 256 MB, video 64MB. Maxim 4 placi intr-un PC (16 canale). Calitate excelenta a imaginii !!	440 lei
	<b>EH9808</b>	Placa DVR 8 canale video, 9 bit PHILIPS ADC, 200 fps, rezolutie 640x480, compresie H.264 (MPEG 4/part10), detectie miASare, control prin LAN, control PTZ, sistem operare WIN 2000/XP, cerinte minime PC: P4 1,7GHz, 256 MB, video 64MB. Maxim 4 placi intr-un PC (32 canale). Calitate excelenta a imaginii !!	550 lei
	<b>VEC-0404F</b>	Placa DVR 4 canale video, 4 canale audio, 100 fps, rezolutie 720x576, compresie hardware H.264 (MPEG 4/part10), detectie miASare, control prin LAN, control PTZ, sistem operare WIN 2000/XP, cerinte minime PC: P4 2.0 GHz, 256 MB RAM. Maxim 4 placi intr-un PC (16 canale). Calitate excelenta a imaginii !!	732 lei
	<b>VEC-0804F</b>	Placa DVR 8 canale video,8 canale audio, 200 fps, rezolutie 720x576, compresie hardware H.264 (MPEG 4/part10), detectie miASare, control prin LAN, control PTZ, sistem operare WIN 2000/XP, cerinte minime PC: P4 2.0 GHz, 256 MB RAM. Maxim 4 placi intr-un PC (32 canale). Calitate excelenta a imaginii !!	1,296 lei
	<b>VEC-1604F</b>	Placa DVR 16 canale video, 16 canale audio, 400 fps, rezolutie 720x576, compresie H.264 (MPEG 4/part10), detectie miASare, control prin LAN, control PTZ, sistem operare WIN 2000/XP, cerinte minime PC: P4 2.0 GHz, 256 MB RAM. Maxim 2 placi intr-un PC (32 canale). Calitate excelenta a imaginii !!	2,400 lei
<b>Inregistratoare digitale (DVR)</b>			

	<b>4C1HD</b>	4 canale, 100 FPS vizionare, 25 FPS inregistrare, inregistrare la detectie de miscare, se poate seta contrastul si luminozitatea pe fiecare canal, compresie <b>MJPEG</b> , trei nivele de calitate la inregistrare, port USB, se poate instala un hard disc.	638 lei
	<b>4C2HD</b>	4 canale, 100 FPS vizionare, 25 FPS inregistrare, inregistrare la detectie de miscare, se poate seta contrastul si luminozitatea pe fiecare canal, compresie <b>MJPEG</b> , trei nivele de calitate la inregistrare, port USB, se pot instala doua hard discuri din care unul pe sina mobila.	711 lei
	<b>4C.H264</b>	4 canale video, un canal audio, 100 FPS vizionare, 100 FPS inregistrare, <b>TRIPLEX</b> , inregistrare la detectie de miscare, compresie hardware <b>H264</b> , port USB, se poate instala un hard disc <b>SATA</b> fara limita de capacitate, backup pe memory stick prin USB, zoom digital, telecomanda, <b>mouse</b> pentru configurare usoara, iesire <b>VGA</b> , port <b>Ethernet</b> pentru acces din <b>Internet</b> , port serial pentru comanda speed dome.	1,400 lei
	<b>MC W 404 IP</b>	4 canale video, un canal audio, 100 FPS vizionare, 50 FPS inregistrare, <b>TRIPLEX</b> , rezolutie vizualizare (640x544), rezolutie inregistrare (640x272), 2 iesiri videocomplex, 1 iesire VGA, 4 intra alarma, 1 iesire alarma, inregistrare la detectie de miscare, compresie duala <b>MJPEG/ MPEG4</b> , port USB, posibilitate control meniuri cu mouse, port <b>Ethernet</b> pentru acces din Internet (compresie <b>MPEG4</b> ), port serial pentru comanda speed dome, <b>CD writer</b> , se pot instala 2 hard discuri.	1,200 lei
	<b>MC 404 IP</b>	4 canale video, un canal audio, 100 FPS vizionare, 50 FPS inregistrare, <b>TRIPLEX</b> , rezolutie vizualizare (640x544), rezolutie inregistrare (640x272), 2 iesiri videocomplex, 1 iesire VGA, 4 intra alarma, 1 iesire alarma, inregistrare la detectie de miscare, compresie duala <b>MJPEG/ MPEG4</b> , port USB, posibilitate control meniuri cu mouse, port <b>Ethernet</b> pentru acces din Internet (compresie <b>MPEG4</b> ), port serial pentru comanda speed dome, se pot instala 2 hard discuri.	1,100 lei
	<b>AUTO DVR</b>	4 canale video, un canal audio, 100 FPS vizionare, 25 FPS inregistrare, inregistrare la detectie de miscare, compresie <b>MJPEG</b> , se poate instala un hard disc pe sina mobile, telecomanda, rezistent la socuri.	1,222 lei
	<b>MC 408 IP</b>	8 canale video, un canal audio, 200 FPS vizionare, 50 FPS inregistrare, <b>TRIPLEX</b> , rezolutie vizualizare (640x544), rezolutie inregistrare (640x272), 2 iesiri videocomplex, 1 iesire VGA, 8 intra alarma, 1 iesire alarma, inregistrare la detectie de miscare, compresie duala <b>MJPEG/ MPEG4</b> , port USB, posibilitate control meniuri cu mouse, port <b>Ethernet</b> pentru acces din Internet (compresie <b>MPEG4</b> ), port serial pentru comanda speed dome, <b>CD writer</b> , se pot instala 2 hard discuri.	1,700 lei
	<b>16C2HDIP</b>	16 canale video, un canal audio, 400 FPS vizionare, 100 FPS inregistrare, <b>TRIPLEX</b> , inregistrare la detectie de miscare, compresie <b>MJPEG</b> , port USB, se pot instala doua hard discuri, telecomanda, port <b>Ethernet</b> pentru acces din <b>Internet</b> , port serial pentru comanda speed dome, <b>CD writer</b> .	2,900 lei

	<b>16C2000</b>	16 canale video, un canal audio, 400 FPS vizionare, 100 FPS inregistrare, <b>TRIPLEX</b> , inregistrare la detectie de miscare, compresie <b>JPEG 2000</b> , port USB, se pot instala doua hard discuri, telecomanda, port <b>Ethernet</b> pentru acces din <b>Internet</b> , port serial pentru comanda speed dome, <b>CD writer, Jog&amp;Shuttle, full Network</b>	3,300 lei
	<b>EDR 404</b>	DVR stand alone, compresie H.264, 4 intrari video, 4 intrari audio, 100 fps (real-time) la vizualizare, 100fps (real-time) la inregistrare, rezolutie vizualizare D1 (704x576), rezolutie inregistrare D1 (704x576), inregistrare la detectie miscare, dupa orar, continuu sau intrari alarma, 4 intrari alarma, 3 iesiri alarma (releu), LAN, webserver, soft client, USB, RS232, RS485 pentru comanda speed domuri, suporta 4 hard disk-uri SATA, 2 iesiri videocomplex 1 iesire VGA, operare triplex, telecomanda, controlul meniurilor cu mouse USB, controlul speed domurilor cu mouse (3D intelligent location), <b>Calitate excelenta a imaginii !!</b>	1,494 lei
	<b>EDR 804</b>	DVR stand alone, compresie H.264, 8 intrari video, 4 intrari audio, 200 fps (real-time) la vizualizare, 200fps (real-time) la inregistrare, rezolutie vizualizare D1 (704x576), rezolutie inregistrare D1 (704x576), inregistrare la detectie miscare, dupa orar, continuu sau intrari alarma, 4 intrari alarma, 3 iesiri alarma (releu), LAN, webserver, soft client, USB, RS232, RS485 pentru comanda speed domuri, suporta 4 hard disk-uri SATA, 2 iesiri videocomplex 1 iesire VGA, operare triplex, telecomanda, controlul meniurilor cu mouse USB, controlul speed domurilor cu mouse (3D intelligent location), <b>Calitate excelenta a imaginii !!</b>	2,900 lei
	<b>EDR 1604</b>	DVR stand alone, compresie H.264, 16 intrari video, 4 intrari audio, 400 fps (real-time) la vizualizare, 400fps (real-time) la inregistrare, rezolutie vizualizare D1 (704x576), rezolutie inregistrare CIF (352x288), inregistrare la detectie miscare, dupa orar, continuu sau intrari alarma, 4 intrari alarma, 3 iesiri alarma (releu), LAN, webserver, soft client, USB, RS232, RS485 pentru comanda speed domuri, suporta 4 hard disk-uri SATA, 2 iesiri videocomplex 1 iesire VGA, operare triplex, telecomanda, controlul meniurilor cu mouse USB, controlul speed domurilor cu mouse (3D intelligent location), <b>Calitate excelenta a imaginii !!</b>	4,500 lei
	<b>EDR 404 HE</b>	DVR stand alone, compresie H.264, 4 intrari video, 4 intrari audio, 100 fps (real-time) la vizualizare, 100fps (real-time) la inregistrare, rezolutie vizualizare D1 (704x576), rezolutie inregistrare D1 (704x576), inregistrare la detectie miscare, dupa orar, continuu sau intrari alarma, 4 intrari alarma, 6 iesiri alarma (releu), LAN, webserver, soft client, 2 porturi USB, RS232, RS485 pentru comanda speed domuri, suporta 8 hard disk-uri SATA (sau 1 unitate optica si 6 hard disk-uri), 2 iesiri videocomplex, 1 iesire VGA, operare triplex, telecomanda, controlul meniurilor cu mouse USB, controlul speed domurilor cu mouse (3D intelligent location). Unitatea optica si hard disk-urile nu sunt incluse. <b>Calitate excelenta a imaginii !!</b>	3,018 lei

